



Upper-Body ergocycle - Cardio 700 series

Structure

- Very rigid, mechanical welded frame
- Electromagnetic braking system using Eddy current
- Transmission by flexible, noiseless belts with automatic strain
- Braking indications from 5 to 160 W (0 to 50 tr/mn)
- Possibility to work in both direction of rotation (with free-wheels)
- Mobile control board
- Power supply 230 V / 50 Hz 16 A (2P+T) consumption 1 A

Electronics

- Display in 5 languages
- Colour "Graphic" screen : LCD display
- Display : Power (Watts), Braking indications (Watts), Speed (tr/mn), Distance (km), Time, Consumed calories, Developed torque (Nm)
- RS 232 Interface

Programming system

- 30 free programmes
- 12 pre-set programmes
- Programme with constant power
- Programme with constant heartbeats
- Possible use in manual mode
- "Polar" compatible heartbeat sensor



12

Models	Cardio 710	Cardio 720	Cardio 750	Cardio 760
Adjustable crank arms in length	-	Yes	-	Yes
Support for wheelchair's access	-	-	Yes	Yes
Assisted height adjustment	-	-	Yes	Yes
Space required (cm)	62x50x63		91x89x144	
Weight (kg)	20		55	

Options

- Wide colour choice (180 shades)
- Thoracic belt
- Adjustable height seat (maximum user weight : 110kg) for Cardio750 and Cardio 760

Standards

- Machine in compliance with EC Standards
- Directive 93/42/CEE (concerning the medical devices)
- Standards : EN 60204/1 - EN 60601/1 - EN 61000/6/3 - EN 61000/6/1

Guarantee

- 5 years guarantee*

Commercial department

RN 6, route de St Bris • BP4 • F - 89290 Champs-sur-Yonne • Phone + 33 (0) 386 53 83 81 •
Fax + 33 (0) 386 53 80 42 • contact@techmed-tm.com • www.techmed-tm.com